



Wed 7/16/2014 12:41 PM

Young, Brad <Brad.Young2@dot.state.oh.us>

Marlee Float Skimmer

To jamie@swfeesaver.com

i This message has been replied to or forwarded.

Jamie,

On 7/8/14 I received your new product submission for your subject product. ODOT has had other skimmer product submitted in the past. Our Hydraulics Construction Engineer offered the following comments for those submissions:

“The Contractor designs the stormwater plan. In the temporary BMP world.....the skimmer device, when required by permit, needs to be incorporated into the overall cost of the sediment pond control structure and NOT a specific add-on. ODOT requires compliance with the permit and doesn’t spec a skimmer per se.”

“The permit only requires a “surface dewatering device”. The Fraircloth Skimmer is one type of device. ODOT points to the Rainwater and Land Development Manual (http://www2.ohiodnr.com/portals/soilwater/pdf/stormwater/3-3-14RLD_All.pdf) for specifications of all the BMP. If the product meets these specs, we allow them for use.”

“Ohio Construction General Permit requires a 48-hour drawdown time for all sediment basins of the calculated water quality volume. This information will be required.”

I hope this provides you some guidance.

Thank you,

Brad Young, P.E.
New Products Engineer
Office of Materials Management
1600 West Broad Street
Columbus, Ohio 43223
Ph: (614)-351-2882
brad.young2@dot.state.oh.us